



UL Product iQ
 UL'S NEXT GENERATION CERTIFICATIONS SEARCH
 The same trusted data in a modern search engine.

**NOW
 AVAILABLE**

▶ LEARN MORE

BAZR2.MH12547
Batteries, Standby - Component

[Page Bottom](#)

Batteries, Standby - Component

[See General Information for Batteries, Standby - Component](#)

EXIDE TECHNOLOGIES GMBH

MH12547

IM THIERGARTEN

63654 BUEDINGEN, GERMANY

Model	Rate		Max Discharge Rate		Max Charge Rate		Oper. Range/ Max Ambient	Battery Case Flame	Enclosure Test	High-rate Discharge Test Current
	Capacity, Ah	Voltage, Vdc	Amps	Hr	Amps	Hr	(°C)	Rating	Schedule	Amps
Secondary sealed cell, lead acid batteries with pressure release vents, "Powerfit SP300 Series"										
SP312/7.0	-	-	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien 4V00Gi Series"										
4V70Gi175	-	-	-	-	-	-	-	-	-	-
4V80Gi200	-	-	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A-RAIL Series"										
SR 12V 105 A	105	12	-	-	-	-	-	-	-	-
SR 12V 105 F10	105	12	-	-	-	-	-	-	-	-
SR 12V 122 A	122	12	-	-	-	-	-	-	-	-
SR 12V 155 FT	155	12	-	-	-	-	-	-	-	-
SR 12V 165 A	165	12	-	-	-	-	-	-	-	-
SR 12V 175 A	175	12	-	-	-	-	-	-	-	-
SR 12V 175 F10	175	12	-	-	-	-	-	-	-	-
SR 12V 180 A	180	12	-	-	-	-	-	-	-	-
SR 12V 240 A	240	12	-	-	-	-	-	-	-	-
SR 12V 33 G	33	12	-	-	-	-	-	-	-	-
SR 12V 40 A	40	12	-	-	-	-	-	-	-	-
SR 12V 51 A	51	12	-	-	-	-	-	-	-	-
SR 12V 55 A	55	12	-	-	-	-	-	-	-	-
SR 12V 61 A	61	12	-	-	-	-	-	-	-	-
SR 12V 61 F10	61	12	-	-	-	-	-	-	-	-
SR 12V 65 A	65	12	-	-	-	-	-	-	-	-
SR 12V 65 G	65	12	-	-	-	-	-	-	-	-
SR 12V 75 A	75	12	-	-	-	-	-	-	-	-
SR 12V 80 A	80	12	-	-	-	-	-	-	-	-
SR 12V 82 A RF	75	12	-	-	-	-	-	-	-	-
SR 12V 85 F10	85	12	-	-	-	-	-	-	-	-
SR 12V 88 A RF	80	12	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A200 Series"										
A204/1.0K	1	4	-	-	-	-	-	-	-	-
A206/1.0S	1	6	-	-	-	-	-	-	-	-
A206/4.0S	4	6	-	-	-	-	-	-	-	-


A206/6.5S	6.5	6	-	-	-	-	-	-	-	-
A208/2.5S	2.5	8	-	-	-	-	-	-	-	-
A208/2.7S	2.7	8	-	-	-	-	-	-	-	-
A208/3.8S	3.8	8	-	-	-	-	-	-	-	-
A212/2.5S	2.5	12	-	-	-	-	-	-	-	-
A212/2.7S	2.7	12	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A400 Series"										
A406/165.0A	165	6	-	-	-	-	-	-	-	-
A406/165.0F10	165	6	-	-	-	-	-	-	-	-
A412/100.0A	100	12	-	-	-	-	-	-	-	-
A412/100.0F10	100	12	-	-	-	-	-	-	-	-
A412/12.0SR	12	12	-	-	-	-	-	-	-	-
A412/120.0A	120	12	-	-	-	-	-	-	-	-
A412/120.0F10	120	12	-	-	-	-	-	-	-	-
A412/120FT	120	12	-	-	-	-	-	-	-	-
A412/170FT	165	12	-	-	-	-	-	-	-	-
A412/180.0A	180	12	-	-	-	-	-	-	-	-
A412/180.0F10	180	12	-	-	-	-	-	-	-	-
A412/20.0G5	20	12	-	-	-	-	-	-	-	-
A412/32.0F10	32	12	-	-	-	-	-	-	-	-
A412/32.0G6	32	12	-	-	-	-	-	-	-	-
A412/5.5SR	5.5	12	-	-	-	-	-	-	-	-
A412/5.5SR V0	5.5	12	-	-	-	-	-	V-0	-	-
A412/50.0A	50	12	-	-	-	-	-	-	-	-
A412/50.0F10	50	12	-	-	-	-	-	-	-	-
A412/50.0G6	50	12	-	-	-	-	-	-	-	-
A412/65.0F10	65	12	-	-	-	-	-	-	-	-
A412/65.0G6	65	12	-	-	-	-	-	-	-	-
A412/8.5SR	8.5	12	-	-	-	-	-	-	-	-
A412/85.0F10	85	12	-	-	-	-	-	-	-	-
A412/90.0A	90	12	-	-	-	-	-	-	-	-
A412/90.0F10	90	12	-	-	-	-	-	-	-	-
PC12/130FT	120	12	-	-	-	-	-	-	-	-
PC12/180FT	165	12	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A400HR Series"										
A412/125 HR	36	12	-	-	-	-	-	-	-	-
A412/125 HR V0	36	12	-	-	-	-	-	-	-	-
A412/150 HR	49.6	12	-	-	-	-	-	-	-	-
A412/150 HR V0	49.6	12	-	-	-	-	-	-	-	-
A412/185 HR	55.2	12	-	-	-	-	-	-	-	-
A412/185 HR V0	55.2	12	-	-	-	-	-	-	-	-
A412/195 HR	60.8	12	-	-	-	-	-	-	-	-
A412/195 HR V0	60.8	12	-	-	-	-	-	-	-	-
A412/270 HR	79.2	12	-	-	-	-	-	-	-	-
A412/270 HR V0	79.2	12	-	-	-	-	-	-	-	-
A412/340 HR	104	12	-	-	-	-	-	-	-	-
A412/340 HR V0	104	12	-	-	-	-	-	-	-	-
A412/370 HR	101	12	-	-	-	-	-	-	-	-
A412/370 HR V0	101	12	-	-	-	-	-	-	-	-
A412/410 HR	118	12	-	-	-	-	-	-	-	-
A412/410 HR V0	118	12	-	-	-	-	-	-	-	-
A412/500 HR	161	12	-	-	-	-	-	-	-	-

A412/500 HR V0	161	12	-	-	-	-	-	-	-	-	-
A412/550 HR	172	12	-	-	-	-	-	-	-	-	-
A412/550 HR V0	172	12	-	-	-	-	-	-	-	-	-
A412/70 HR	21.6	12	-	-	-	-	-	-	-	-	-
A412/95 HR	27.2	12	-	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A400RAIL Series"											
A412/100 SR	100	12	-	-	-	-	-	-	-	-	-
A412/12 SR	12	12	-	-	-	-	-	-	-	-	-
A412/120 SR	120	12	-	-	-	-	-	-	-	-	-
A412/180 SR	180	12	-	-	-	-	-	-	-	-	-
A412/20 SR	20	12	-	-	-	-	-	-	-	-	-
A412/32 SR	32	12	-	-	-	-	-	-	-	-	-
A412/5.5 SR	5.5	12	-	-	-	-	-	-	-	-	-
A412/50 SR	50	12	-	-	-	-	-	-	-	-	-
A412/65 SR	65	12	-	-	-	-	-	-	-	-	-
A412/8.5 SR	8.5	12	-	-	-	-	-	-	-	-	-
A412/90 SR	90	12	-	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A500 Series"											
A502/10.0S	10	2	-	-	-	-	-	-	-	-	-
A504/3.5S	3.5	4	-	-	-	-	-	-	-	-	-
A506/1.2S	1.2	6	-	-	-	-	-	-	-	-	-
A506/10.0S	10	6	-	-	-	-	-	-	-	-	-
A506/3.5S	3.5	6	-	-	-	-	-	-	-	-	-
A506/4.2S	4.2	6	-	-	-	-	-	-	-	-	-
A506/4S	-	-	-	-	-	-	-	-	-	-	-
A506/6.5S	6.5	6	-	-	-	-	-	-	-	-	-
A508/3.5S	3.5	8	-	-	-	-	-	-	-	-	-
A512/1.2S	1.2	12	-	-	-	-	-	-	-	-	-
A512/10.0S	10	12	-	-	-	-	-	-	-	-	-
A512/115.0A	115	12	-	-	-	-	-	-	-	-	-
A512/120A	120	12	-	-	-	-	-	-	-	-	-
A512/140A	140	12	-	-	-	-	-	-	-	-	-
A512/15G	-	-	-	-	-	-	-	-	-	-	-
A512/16.0G5	16	12	-	-	-	-	-	-	-	-	-
A512/2.0S	2	12	-	-	-	-	-	-	-	-	-
A512/200A	200	12	-	-	-	-	-	-	-	-	-
A512/24.0G5	24	12	-	-	-	-	-	-	-	-	-
A512/25.0G5	25	12	-	-	-	-	-	-	-	-	-
A512/3.5S	3.5	12	-	-	-	-	-	-	-	-	-
A512/30.0G6	30	12	-	-	-	-	-	-	-	-	-
A512/40.0A	40	12	-	-	-	-	-	-	-	-	-
A512/40.0G6	40	12	-	-	-	-	-	-	-	-	-
A512/55.0A	55	12	-	-	-	-	-	-	-	-	-
A512/6.5S	6.5	12	-	-	-	-	-	-	-	-	-
A512/60.0A	60	12	-	-	-	-	-	-	-	-	-
A512/60.0G6	60	12	-	-	-	-	-	-	-	-	-
A512/65.0A	65	12	-	-	-	-	-	-	-	-	-
A512/65.0G6	65	12	-	-	-	-	-	-	-	-	-
A512/85.0A	85	12	-	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A600 Series"											
A602/1000 - 10 OPzV 1000	1248	2	-	-	-	-	-	-	-	-	-
A602/1010 - 8 OPzV 800	998	2	-	-	-	-	-	-	-	-	-

A602/1200 - 12 OPzV 1200	1497	2	-	-	-	-	-	-	-	-
A602/1250 - 10 OPzV 1000	1248	2	-	-	-	-	-	-	-	-
A602/1500 - 12 OPzV 1500	1643	2	-	-	-	-	-	-	-	-
A602/1510 - 12 OPzV 1200	1497	2	-	-	-	-	-	-	-	-
A602/1650 - 12 OPzV 1500	1643	2	-	-	-	-	-	-	-	-
A602/1650 C - 12 OPzV 1500 compact	1643	2	-	-	-	-	-	-	-	-
A602/2000 - 16 OPzV 2000	2190	2	-	-	-	-	-	-	-	-
A602/2200 - 16 OPzV 2000	2190	2	-	-	-	-	-	-	-	-
A602/225 - 4 OPzV 200	224	2	-	-	-	-	-	-	-	-
A602/250 - 5 OPzV 250	280	2	-	-	-	-	-	-	-	-
A602/2500 - 20 OPzV 2500	2738	2	-	-	-	-	-	-	-	-
A602/2740 - 20 OPzV 2500	2738	2	-	-	-	-	-	-	-	-
A602/280 - 5 OPzV 250	280	2	-	-	-	-	-	-	-	-
A602/300 - 6 OPzV 300	337	2	-	-	-	-	-	-	-	-
A602/3000 - 24 OPzV 3000	3286	2	-	-	-	-	-	-	-	-
A602/3300 - 24 OPzV 3000	3286	2	-	-	-	-	-	-	-	-
A602/335 - 6 OPzV 300	337	2	-	-	-	-	-	-	-	-
A602/350 - 5 OPzV 350	416	2	-	-	-	-	-	-	-	-
A602/415 - 5 OPzV 350	416	2	-	-	-	-	-	-	-	-
A602/420 - 6 OPzV 420	499	2	-	-	-	-	-	-	-	-
A602/490 - 7 OPzV 490	582	2	-	-	-	-	-	-	-	-
A602/500 - 6 OPzV 420	499	2	-	-	-	-	-	-	-	-
A602/580 - 7 OPzV 490	582	2	-	-	-	-	-	-	-	-
A602/600 - 6 OPzV 600	748	2	-	-	-	-	-	-	-	-
A602/750 - 6 OPzV 600	748	2	-	-	-	-	-	-	-	-
A602/800 - 8 OPzV 800	998	2	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A600 Solar Series"										
A602/1130 Solar - 8 OPzV 1130	1131	2	-	-	-	-	-	-	-	-
A602/1200 Solar - 10 OPzV 1200	1200	2	-	-	-	-	-	-	-	-
A602/1400 Solar - 12 OPzV 1400	1400	2	-	-	-	-	-	-	-	-
A602/1415 Solar - 10 OPzV 1415	1413	2	-	-	-	-	-	-	-	-
A602/1695 Solar - 12 OPzV 1695	1695	2	-	-	-	-	-	-	-	-
A602/1700 Solar - 12 OPzV 1700	1700	2	-	-	-	-	-	-	-	-
A602/1960 C Solar - 12 OPzV 1960 compact	1959	2	-	-	-	-	-	-	-	-
A602/1960 Solar - 12 OPzV 1960	1959	2	-	-	-	-	-	-	-	-
A602/2300 Solar - 16 OPzV 2300	2300	2	-	-	-	-	-	-	-	-
A602/240 Solar - 4 OPzV 240	240	2	-	-	-	-	-	-	-	-
A602/2600 Solar - 16 OPzV 2600	2613	2	-	-	-	-	-	-	-	-
A602/2900 Solar - 20 OPzV 2900	2900	2	-	-	-	-	-	-	-	-
A602/295 Solar - 4 OPzV 295	294	2	-	-	-	-	-	-	-	-
A602/300 Solar - 5 OPzV 300	300	2	-	-	-	-	-	-	-	-
A602/3270 Solar - 20 OPzV 3270	3266	2	-	-	-	-	-	-	-	-
A602/3500 Solar - 24 OPzV 3500	3500	2	-	-	-	-	-	-	-	-
A602/360 Solar - 6 OPzV 360	360	2	-	-	-	-	-	-	-	-
A602/370 Solar - 5 OPzV 370	367	2	-	-	-	-	-	-	-	-
A602/3920 Solar - 24 OPzV 3920	3919	2	-	-	-	-	-	-	-	-
A602/400 Solar - 5 OPzV 400	400	2	-	-	-	-	-	-	-	-
A602/440 Solar - 6 OPzV 440	440	2	-	-	-	-	-	-	-	-
A602/500 Solar - 6 OPzV 500	500	2	-	-	-	-	-	-	-	-
A602/520 Solar - 5 OPzV 520	519	2	-	-	-	-	-	-	-	-
A602/600 Solar - 7 OPzV 600	600	2	-	-	-	-	-	-	-	-

A602/625 Solar - 6 OPzV 625	623	2	-	-	-	-	-	-	-	-	-
A602/720 Solar - 6 OPzV 720	720	2	-	-	-	-	-	-	-	-	-
A602/750 Solar - 7 OPzV 750	727	2	-	-	-	-	-	-	-	-	-
A602/850 Solar - 6 OPzV 850	848	2	-	-	-	-	-	-	-	-	-
A602/960 Solar - 8 OPzV 960	960	2	-	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien A700 Series"											
A704/245	245	4	-	-	-	-	-	-	-	-	-
A704/280	280	4	-	-	-	-	-	-	-	-	-
A706/105	105	6	-	-	-	-	-	-	-	-	-
A706/126	126	6	-	-	-	-	-	-	-	-	-
A706/140	140	6	-	-	-	-	-	-	-	-	-
A706/175	175	6	-	-	-	-	-	-	-	-	-
A706/21	21	6	-	-	-	-	-	-	-	-	-
A706/210	210	6	-	-	-	-	-	-	-	-	-
A706/42	42	6	-	-	-	-	-	-	-	-	-
A706/63	63	6	-	-	-	-	-	-	-	-	-
A706/84	84	6	-	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien Solar Bloc Series"											
S12/130V	130	12	-	-	-	-	-	-	-	-	-
S12/17G5	17	12	-	-	-	-	-	-	-	-	-
S12/230A	230	12	-	-	-	-	-	-	-	-	-
S12/27G5	27	12	-	-	-	-	-	-	-	-	-
S12/32G6	32	12	-	-	-	-	-	-	-	-	-
S12/41A	41	12	-	-	-	-	-	-	-	-	-
S12/6.6S	6.6	12	-	-	-	-	-	-	-	-	-
S12/60A	60	12	-	-	-	-	-	-	-	-	-
S12/85A	85	12	-	-	-	-	-	-	-	-	-
S12/90V	90	12	-	-	-	-	-	-	-	-	-
SB12/100A	100	12	-	-	-	-	-	-	-	-	-
SB12/130A	130	12	-	-	-	-	-	-	-	-	-
SB12/185A	185	12	-	-	-	-	-	-	-	-	-
SB12/60A	60	12	-	-	-	-	-	-	-	-	-
SB12/75A	75	12	-	-	-	-	-	-	-	-	-
SB6/200A	200	6	-	-	-	-	-	-	-	-	-
SB6/330A	330	6	-	-	-	-	-	-	-	-	-
Secondary sealed cell, lead acid batteries with pressure release vents, "Sonnenschien Traction Block Series"											
GF6V-160V1	160	6	-	-	-	-	-	-	-	-	-
GF6V-160VP	160	6	-	-	-	-	-	-	-	-	-

Note - Batteries plastic with V-0 rating will have suffix V0.

Marking: Company name, model designation and the Recognized Component Mark,  .
 Last Updated on 2017-12-19

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".